


Safety Data Sheet

1. Identification

Product Name	ADX-1325 Natural	
Product Description	Impact-modified polypropylene compound	
Physical Appearance	White, opaque solid plastic pellets, approximately 1/8" – 3/8" (3mm – 10mm) in diameter, with slight to no odor	
Recommended Use	Injection molding. Intended for commercial use only.	
Manufacturer	Advanced Composites, Inc. www.advcmp.com	
Telephone Number	+1 (937) 575-9800	
Address	Ohio Plant 1062 S. 4th Ave. Sidney, OH 45365	Tennessee Plant 3066 Sidco Drive Nashville, TN 37204
24 HR. Emergency Contact Number	CHEMTREC (USA) +1 (800) 424-9300	

2. Hazard(s) Identification

Emergency Overview	
Hazard Classification (GHS-US)	Not classified as hazardous.
Pictograms	
Signal Word	WARNING
Hazards	Spilled pellets pose a slip hazard. Dust accumulation may cause explosions. High temperature processing fumes may be irritating to the eyes, nose, throat, and skin. May contain quartz. Quartz dust has caused cancer and lung disease in workers that inhale it over an extended period of time. However, inhalation of quartz dust from this product is not deemed likely due to the plastic resin form.
Precautionary Statement	Maintain adequate ventilation to prevent accumulation of dust and fumes from processing. Dust created during handling or processing may be mildly irritating to the respiratory system. Keep away from sources of ignition. In solid form, this polymer product is not considered to be a health hazard, although the pellets and the dust generated from them may be mildly irritating to the skin and eyes by mechanical action. If swallowed, polymer may pose possible intestinal obstruction.
Irritancy	When heated, this polymer may release fumes and/or vapors that are irritating to the eyes, nose, throat, and skin. Overexposure to fumes or vapors may also cause headache, nausea, shortness of breath, and cough.

Safety Data Sheet

3. Composition/Information on Ingredients

Component(s)	CAS Registry #	Weight %
Ethylene-propylene-copolymer	9010-79-1	†
Talc (Magnesium Silicate)	14807-96-6	≤ 1.0
Quartz (Crystalline silica, component of talc)	14808-60-7	≤ 1.0
† Proprietary information		
Comments	The listed components (if present in this product) are encapsulated in a thermoplastic resin with limited release under normal conditions of use, transportation, and storage. Increased release may occur when the resin (or material/product manufactured from it) is subject to grinding, polishing, excessive heat, or other processes which enhance the potential for the generation of particulates, fumes, and/or vapors. A qualified health specialist should evaluate the specific potential for release under user's conditions of handling of this material.	

4. First-Aid Measures

Most Important Effects	Molten plastic can cause severe thermal burns.
First Aid	
Skin Contact	If skin irritation or rash occurs, rinse or wash affected areas. Seek medical advice/attention if irritation persists. If contacted by molten polymer, cool immediately with cold or ice water. Do not attempt removal of any solidified material without medical assistance. Get medical attention immediately. In the case of most burns, it may be advisable to allow solidified material to slough off on its own. Attempted removal may lead to more damage of the skin and underlying tissue. If removal is indicated (e.g. solidified material is located on a critical part of the hand or face), removal with mineral oil is recommended.
Eye Contact	If contacted by molten polymer, immediately flush eyes with plenty of cool water for at least 15 minutes. Do not rub eyes. Get medical attention immediately.
Ingestion	If product is ingested, contact a physician or the Poison Control Center as appropriate whenever any foreign object is swallowed. Rinse mouth. Do NOT induce vomiting.
Inhalation	If irritation or dizziness occurs, evacuate to fresh air and remain at rest in a comfortable position for breathing. Seek medical advice/attention.
Acute and Delayed Effects	
Skin Contact	Prolonged exposure may cause irritation, rash, or allergic skin reaction. Wash hands, other exposed areas, and clothing regularly. Seek medical advice if conditions persist.
Eye Contact, Inhalation	Dust and fumes may cause irritation to the eyes, nose, throat, and lungs. Flush eyes with water or get to fresh air. Seek medical attention if irritation persists.
Ingestion	May cause intestinal obstruction.

Safety Data Sheet

5. Fire-Fighting Measures

Flammable Properties	
Flammable Class	Class 1 – Must be heated to burn Please use caution when handling material near open flame. Material will ignite when exposed to direct flame, but will not burn readily.
Flash Point	Not established.
Autoignition Temperature	>280°C (>536°F), ASTM E659
Protective Equipment for Firefighters	Fire fighters should wear self-contained breathing apparatus in the positive pressure mode with a full-face piece when there is a possibility of exposure to smoke, fumes, or hazardous decomposition products.
Suitable Extinguishing Media	<ul style="list-style-type: none"> ✓ Water spray ✓ Dry chemical ✓ Foam ✓ Carbon dioxide
Fire Fighting Procedures	<p>If possible, water should be applied as a spray from a fogging nozzle since this polymer is a surface burning material. The application of high velocity water will spread the burning layer.</p> <p>NOTE: Individuals should perform only those fire-fighting procedures for which they have been trained.</p>
Hazardous Combustion Products	Carbon, oxides of carbon, oxides of nitrogen, water, acrolein, formaldehyde, other aldehydes, ketones, alcohols, fatty acids, methane, ethane, acetylene, other organic vapors and fumes.

6. Accidental Release Measures

Personal Precautions	Restrict access to only authorized personnel wearing appropriate personal protective equipment. Spilled pellets pose a slip hazard.
Environmental Precautions	Keep spilled material away from heat, sparks, and open flames. Ensure adequate ventilation.
Protective Equipment	Wear safety glasses meeting the specifications of OSHA 29CFR 1910.133/ ANSI Standard Z87.1 where no contact with the eye is anticipated. Chemical safety goggles meeting the specifications of OSHA 29CFR 1019.133/ ANSI Standard Z87.1 should be worn whenever there is a possibility of contact with the eyes.
General Procedures	Where spills are possible, a comprehensive spill release response plan should be developed and implemented. Plastic pellets are listed as “significant materials” by US EPA (40CFR 122.26(b)(12)) and may need to be discussed in an application for a storm water discharge permit.
Small Spill	Small spills can be swept up and recycled or disposed of.

Safety Data Sheet

Large Spill

Wear appropriate respiratory protection and protective clothing as described in Section 8. Contain spilled material. Transfer to secure containers. In the event of an uncontrolled release of this material, the user should determine if the release is reportable under the applicable laws and regulations.

7. Handling & Storage

Handling

The handling of pellets in both loading and unloading operations as well as fabrication may cause dust to be formed and necessary precautions for personal protection (see Section 8) should be taken. When transferring pellets, precautions such as grounding and bonding can prevent the buildup of static electricity.

Safe Storage

Store in a dry place away from moisture, excessive heat, and sources of ignition. Have emergency equipment for fires and spills readily available.

Incompatible Materials

Do not store with strong oxidizing agents such as nitric acid, sulfuric acid, halogens, hydrogen peroxide, and chlorinating agents.

Hygiene

Wash hands before eating, drinking, smoking, or using the restroom

Further Advice

Keep containers closed and/or covered when not in use.

8. Exposure Controls & Personal Protection

Engineering Controls

Ensure all national/local regulations are observed. Ensure adequate ventilation, especially in confined areas. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Personal Protective Equipment

Skin

Wear heat protective gloves and clothing if there is a potential for contact with heated material.

Eyes and Face

Wear safety glasses meeting the specifications of OSHA 29CFR 1910.133/ ANSI Standard Z87.1 where no contact with the eye is anticipated. Chemical safety goggles meeting the specifications of OSHA 29CFR 1019.133/ ANSI Standard Z87.1 should be worn whenever there is a possibility of contact with the eyes.

Respiratory

Use a NIOSH-approved respirator whenever exposure may exceed established Occupational Exposure Limits.

Safety Data Sheet

Occupational Exposure Limits

Component	Classification	Exposure Limit
Talc (Magnesium Silicate) (14807-96-6)	ACGIH TWA	2 mg/m ³ (particulate matter containing no asbestos and <1% crystalline silica, respirable fraction)
	ACGIH Category	Not classifiable as a Human Carcinogen containing no asbestos fibers
	NIOSH IREL (TWA)	2 mg/m ³ (containing no asbestos and <1% quartz-respirable dust)
	ILDH	1,000 mg/m ³ (containing no asbestos and <1% quartz)
Quartz (Crystalline Silica) (14808-60-7)	ACGIH TWA	0.025 mg/m ³ (respirable fraction)
	ACGIH Category	A2 – Suspected Human Carcinogen
	NIOSH REL (TWA)	0.05 mg/m ³ (respirable dust)
	IDLH	50 mg/m ³ (respirable dust)
	OSHA PEL (STEL)	250 mppcf/%SiO ₂ +5, 10mg/m ³ /%SiO ₂ +2

9. Physical & Chemical Properties

Appearance	Plastic pellets, approximately 1/8" – 3/8" (3mm – 10mm) in diameter
Color	White, Opaque
Odor	Slight to no odor
pH	Not applicable
Melting Point	160~205°C (320~401°F)
Boiling Point	None
Flash Point	No data available
Evaporation Rate	No data available
Flammability	Will ignite when exposed to direct flame, but will not burn readily.
Upper/Lower Explosive Limit	Not explosive
Vapor Pressure	No data available
Vapor Density	No data available
Relative Density	0.89 – 1.30
Water Solubility	Not soluble
Auto-ignition Temperature	>280°C (>536°F), ASTM E659
Decomposition Temperature	No data available
Viscosity	Not applicable

The physical property data above are typical values and should not be construed as a product specification.

Safety Data Sheet

10. Stability & Reactivity

Reactivity	Stable under recommended storage conditions (See Section 7)
Conditions to Avoid	Avoid excessive heat, sparks, or open flame. Keep away from strong oxidizing agents.
Materials to Avoid	May burn or react violently with fluorine/oxygen mixtures with 50~100% fluorine.
Chemical Stability	May be decomposed by strong oxidizing agents such as nitric acid, sulfuric acid, halogens, hydrogen peroxide, and chlorinating agents.
Hazardous Polymerization	Not likely under recommended storage conditions.
Hazardous Decomposition	Combustion may produce carbon, oxides of carbon, oxides of nitrogen, water, acrolein, formaldehyde, other aldehydes, ketones, alcohols, fatty acids, methane, ethane, acetylene, other organic vapors and fumes.

11. Toxicological Information

Primary Route(s) of Exposure	Eye and Skin Contact					
Potential Health Effects						
Eye Contact	May cause irritation from mechanical abrasion.					
Skin	Pellets not expected to cause skin irritation. Contact with molten material may cause thermal burns.					
Inhalation	Not a likely route of exposure. Process fumes may cause irritation.					
Ingestion	May pose a choking hazard if swallowed.					
Immediate Effects	Exposure during handling and processing may aggravate disorders of the eyes, skin, gastrointestinal tract, and respiratory system.					
Delayed Effects	There is no information on the long term health effects of exposure to this product or the fumes and dust that may result from the handling and processing of it.					
Acute Toxicity	<table border="1"> <thead> <tr> <th>Component</th> <th>Measured Toxicity</th> </tr> </thead> <tbody> <tr> <td>Quartz (14808-60-7)</td> <td>LD50: > 5000 mg/kg (Oral, Rat) LD50: > 5000 mg/kg (Dermal, Rat)</td> </tr> </tbody> </table>	Component	Measured Toxicity	Quartz (14808-60-7)	LD50: > 5000 mg/kg (Oral, Rat) LD50: > 5000 mg/kg (Dermal, Rat)	
Component	Measured Toxicity					
Quartz (14808-60-7)	LD50: > 5000 mg/kg (Oral, Rat) LD50: > 5000 mg/kg (Dermal, Rat)					
Carcinogenicity	OSHA, IARC, and NTP have listed quartz (crystalline silica, naturally occurring in talc in low percentages) as a known human carcinogen. These components are essentially bound to the plastic matrix and are unlikely to contribute to workplace exposure under recommended processing conditions.					
Reproductive Toxicity	Not classified					
Medical Conditions Aggravated	There are no known medical conditions aggravated by exposure to this product. However, certain sensitive individuals with respiratory impairments may be affected by exposure to components in the processing emissions.					

Safety Data Sheet

12. Ecological Information

Ecotoxicity	No data is available on the adverse environmental effects of this product. Ecotoxicity is expected to be low due to the limited water solubility of polymers. However, birds, fish, and other wildlife may eat pellets that may obstruct their intestinal tracts.
Persistence and degradability	This material is generally inert and insoluble and is not expected to have any adverse effect on the environment. This material may deteriorate by a number of mechanisms including photo- and thermo-oxidative degradation. Photodegraded polymers are also more easily biodegraded.
Bioaccumulation potential	No data available.
Mobility in soil	No data available.
Other adverse effects	No data available.

13. Disposal Considerations

Product Disposal	All recovered material should be packaged, labeled, transported, and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with good engineering practices. Reclaim where possible.
------------------	---

14. Transport Information

This product is NOT regulated as a hazardous material/dangerous good for all forms of transportation	
In Accordance with DOT	Not regulated for transport
In Accordance with IMDG	Not regulated for transport
In Accordance with IATA	Not regulated for transport
UN Number	None
UN Proper Shipping Name	None
Transport Hazard Class(es)	None
Packing Group	None
Special precautions to be aware of or comply with	None

Safety Data Sheet

15. Regulatory Information

United States	SARA TITLE III (Superfund Amendments and Reauthorization Act)*	
	Fire	No
	Pressure	No
	Reactivity	No
	Acute	No
	Chronic	No
	302/304	This product does not contain chemicals regulated under SARA 302/304.
	311/312 Hazard Categories	This product does not meet the criteria of any SARA hazard categories.
313 Toxic Release	This product does not contain any chemicals listed under SARA 313.	

* **Title III Notes:** This product contains no SARA "toxic chemicals" above threshold levels.

State Regulations

California	Known to the state of California to cause cancer:				
	<table border="1"> <thead> <tr> <th>CAS Registry</th> <th>Component</th> </tr> </thead> <tbody> <tr> <td>14808-60-7</td> <td>Quartz (Airborne particles of respirable size)*</td> </tr> </tbody> </table>	CAS Registry	Component	14808-60-7	Quartz (Airborne particles of respirable size)*
CAS Registry	Component				
14808-60-7	Quartz (Airborne particles of respirable size)*				

* **Note:** The listed component(s) contained in this compound (if any) are encapsulated in a thermoplastic resin with limited release under normal conditions of use, transportation, and storage. See Section 3 for comments on content and release.

Massachusetts New Jersey Pennsylvania	May contain the following chemicals listed as "Right to Know" in these states:						
	<table border="1"> <thead> <tr> <th>CAS Registry</th> <th>Component</th> </tr> </thead> <tbody> <tr> <td>14807-96-6</td> <td>Talc (Magnesium Silicate)*</td> </tr> <tr> <td>14808-60-7</td> <td>Quartz*</td> </tr> </tbody> </table>	CAS Registry	Component	14807-96-6	Talc (Magnesium Silicate)*	14808-60-7	Quartz*
CAS Registry	Component						
14807-96-6	Talc (Magnesium Silicate)*						
14808-60-7	Quartz*						

* **Note:** The listed component(s) contained in this compound (if any) are encapsulated in a thermoplastic resin with limited release under normal conditions of use, transportation, and storage. See Section 3 for comments on content and release.

International Regulation	All ingredients of this compound are listed on the following inventories or are exempt from listing:																		
	<table border="1"> <thead> <tr> <th>Country</th> <th>Notification Listing</th> </tr> </thead> <tbody> <tr> <td>Australia</td> <td>AICS</td> </tr> <tr> <td>Canada</td> <td>DSL</td> </tr> <tr> <td>China</td> <td>IECS</td> </tr> <tr> <td>European Union</td> <td>EINECS</td> </tr> <tr> <td>Japan</td> <td>ENCS/ISHL</td> </tr> <tr> <td>Korea</td> <td>ECL</td> </tr> <tr> <td>New Zealand</td> <td>NZIoC</td> </tr> <tr> <td>United States</td> <td>TSCA</td> </tr> </tbody> </table>	Country	Notification Listing	Australia	AICS	Canada	DSL	China	IECS	European Union	EINECS	Japan	ENCS/ISHL	Korea	ECL	New Zealand	NZIoC	United States	TSCA
Country	Notification Listing																		
Australia	AICS																		
Canada	DSL																		
China	IECS																		
European Union	EINECS																		
Japan	ENCS/ISHL																		
Korea	ECL																		
New Zealand	NZIoC																		
United States	TSCA																		

General Comments The regulatory information presented here should not necessarily be considered as all-inclusive. Other local, state, federal, and international regulations may also apply.

Safety Data Sheet

16. Other Information

Revision Date June 11, 2015

Prepared By Advanced Composites, Inc.

Manufacturer Disclaimer

The information presented herein has been obtained from sources believed to be reliable. However, because of the possibility of human or mechanical error by our sources, Advanced Composites Inc., or others, Advanced Composites Inc. does not guarantee the accuracy, adequacy, or completeness of any information, and is not responsible for any errors or omissions or for any results obtained from the use of such information. We assume no liability or responsibility, expressed or implied, for errors or omissions of any kind, and no warranties or merchantability or fitness, expressed or implied, is made or is to be implied. Consequently, each user should review the information to determine whether it is adequate and appropriate to all aspects of your intended use of this material.

END OF DOCUMENT